



Product Service

CERTIFICATE

No. Z1A 015642 0162 Rev. 00

Holder of Certificate: **Watkins Manufacturing Corp.**

1280 Park Center Drive
Vista CA 92081
USA

Certification Mark:



Product: **Whirlpool spa**

Tested according to:

EN 60335-1:2012/A15:2021
EN 60335-2-60:2003/A12:2010
EN 62233:2008
AfPS GS 2019:01 PAK

With this certificate, in its capacity as a notified GS body, TÜV SÜD Product Service GmbH issues the GS Mark to the named certificate holder for the declared product with the named model designation in accordance with section 20 ProdSG (German Product Safety Act). The product meets the safety and health requirements of section 20 (3) ProdSG. The manufacturer is reminded of their obligations in accordance with section 24 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 095-72196827-000

Valid until: 2030-06-26

Date, 2025-08-04

(Adrian Rabago Valenzuela)

CERTIFICATE

No. Z1A 015642 0162 Rev. 00

Model(s):

Utopia Series, Paradise Series, Vacanza Series,
See Next Pages for Full List of Models

Brand Name:

CalderaSpas, HotSpring, Garden Leisure, HOT SPOT,
FREEFLOW, FANTASY, American Hydrotherapy Systems,
ISLANDER SPAS, AQUATERRA

Parameters:

Input Voltage:	220-240 VAC
Input Frequency:	50 Hz
Input Current:	See following pages for details
Protection Class:	I
Degree of Protection:	IPX5
Ambient Temperature:	45°C Max
Altitude:	2000 m Max

No. Z1A 015642 0162 Rev. 00

CERTIFICATE

No. Z1A 015642 0162 Rev. 00

Model	Size L x W x H (m)	Input Current (A)	Water Capacity (L)	Mass Filled (kg)	No. of Pumps (Hp)
ENVOY, KKE, KKNE	2.36 x 2.31 x 0.97	20 A	1475	2530	2 – 2.5
ARIA, ARE, ARNE	2.20 x 2.20 x 0.91	20 A	1225	2196	2 – 2.0 / 2.5
Limelight Series:					
GLOW, GLWE	1.93 x 2.13 x 0.84	16 A	946	1907	1 – 2.5
FLAIR, FLRE	2.13 x 2.13 x 0.91	16 A	992	2032	2 – 2.0 / 2.0
PULSE, PLSE	2.26 x 2.26 x 0.97	20 A	1230	2200	2 – 2.5 / 2.5
PULSE DL, PLSDE	2.26 x 2.26 x 0.97	20 A	1230	2200	2 – 2.5 / 2.5
BOLT, BLTE	2.03 x 2.03 x 0.84	16 A	1098	1759	1 – 2.0
GLEAM, GLME	2.79 x 2.31 x 0.97	10-12 A / 25 A / 12 A	2082	3130	3/2.5/2.5/2.5
FLASH	2.13 x 2.13 x 0.91	16 A	1365	3080	2/2.0/2.0
Strobe, STBE, STRBE	2.08 x 1.96 x 0.84	16 A	1020	1715	1 – 2.5
BEAM	2.03 x 2.03 x 0.84	16 A	1115	1750	1/2.5
PRISM	2.79 x 2.31 x 0.97	10-12 A / 25 A (optional 12 A)	1990	2225	3/2.5/2.5/2.5
HOT SPOT Series:					
TEMPO	2.26 x 2.26 x 0.97	20 A	1514	2683	2 – 2.5 / 2.5
RELAY	2.13 x 2.13 x 0.91	16 A	1363	2103	2 – 2.0 / 2.0
RHYTHM	2.13 x 2.13 x 0.91	16 A	1363	2103	2 – 2.0 / 2.0
PROPEL	2.08 x 2.08 x 0.84	16 A	1287	1990	1 – 2.5
STRIDE	2.13 x 1.65 x 0.74	16 A	852	1365	1 – 2.0
SX	1.83 x 1.83 x 0.84	16 A	1078	3427	1 – 2.5
TX	1.74 x 1.74 x 0.74	16 A	530	854	1 – 2.0

Trademark: Garden Leisure

- Model or Series name can be followed by suffix "E" or "EXP" to indicate exported models.

Model	Size L x W x H (m)	Input Current (A)	Water Capacity (L)	Mass Filled (kg)	No. of Pumps (Hp)
Garden-696L	2.26 x 2.26 x 0.91	32 A	1,548	2463	2 – 2.5 / 2.5
Garden-680L	2.13 x 2.13 x 0.91	32 A	1,382	2248	2 – 2.5 / 2.5
Garden-780	2.13 x 2.13 x 0.91	32 A	1,389	2335	2 – 2.5 / 2.5
Garden-642L	2.13 x 2.13 x 0.91	13 A	1,185	2106	1 – 2.5
Garden-742	2.13 x 2.13 x 0.91	13 A	1,249	2189	1 – 2.5
Garden-540DL	2.14 x 2.14 x 0.92	20 A	1250	2100	1 – 2.5
Garden-542DL	2.14 x 2.14 x 0.92	20 A	1250	2100	1 – 2.5
Garden-334L	1.65 x 2.13 x 0.75	13 A	795	1345	1 – 2.5

Trademark: FREEFLOW

- Model or Series name can be followed by suffix "E" or "EXP" to indicate exported models.

Model	Size L x W x H (m)	Input Current (A)	Water Capacity (L)	Mass Filled (kg)	No. of Pumps (Hp)
Solstice	2.18 x 1.96 x 0.86	13 A (optional 20 A)	1292	1497	1 - 2.0
Excursion	2.18 x 1.96 x 0.86	13 A (optional 20 A)	1292	1497	1 - 2.0
Accent	2.03 x 1.57 x 0.81	13 A (optional 20 A)	1026	1196	1 - 2.0
Calistoga	1.98 x 1.98 x 0.86	13 A (optional 20 A)	1064	1237	1 - 2.0
Monterey	2.03 x 1.96 x 0.81	13 A (optional 20 A)	1292	1497	1 - 2.0
Azure	2.03 x 1.57 x 0.81	13 A (optional 20 A)	1026	1178	1 - 2.0

CERTIFICATE

No. Z1A 015642 0162 Rev. 00

Model	Size L x W x H (m)	Input Current (A)	Water Capacity (L)	Mass Filled (kg)	No. of Pumps (Hp)
Tristar	1.83 x 1.83 x 0.79	13 A (optional 20 A)	855	989	1 - 2.0
Cascina	1.78 x 1.55 x 0.81	13 A (optional 20 A)	722	827	1 - 2.0
Aptos	1.98 x 1.98 x 0.85	13 A (optional 20 A)	1064	1237	1 - 2.0
Aptos Premier	1.98 x 1.98 x 0.86	13 A (optional 20 A)	1003	1166	1 - 2.0
Mini	1.83 x 1.19 x 0.71	13 A (optional 20 A)	435	564	1 - 2.0
Accolade	2.18 x 1.96 x 0.86	13 A (optional 20 A)	1292	1497	1 - 2.0

Trademark: FANTASY

- Model or Series name can be followed by suffix "E" or "EXP" to indicate exported models.

Model	Size L x W x H (m)	Input Current (A)	Water Capacity (L)	Mass Filled (kg)	No. of Pumps (Hp)
Splendor	1.98 x 1.98 x 0.86	13 A	1064	1237	1 - 2.0
Embrace	1.83 x 1.83 x 0.79	13 A	855	989	1 - 2.0
Drift	1.78 x 1.55 x 0.81	13 A	722	827	1 - 2.0
Entice	1.76 x 2.06 x 0.77	13 A	1026	1178	1 - 2.0
Entice Premier	2.18 x 1.96 x 0.84	13 A	1050	1240	1 - 2.0
Enamor	2.06 x 1.60 x 0.84	13 A	925	1085	1 - 2.0
Enamor Premier	2.06 x 1.60 x 0.84	13 A	925	1085	1 - 2.0
Splendor Premier	1.98 x 1.98 x 0.86	13 A	1003	1166	1 - 2.0
Aspire	1.83 x 1.19 x 0.71	13 A	435	564	1 - 2.0

Trademark: American Hydrotherapy Systems

- Model or Series name can be followed by suffix "E" or "EXP" to indicate exported models.

Model	Size L x W x H (m)	Input Current (A)	Water Capacity (L)	Mass Filled (kg)	No. of Pumps (Hp)
Typhoon	2.21 x 1.95 x 0.86	13 A (optional 20 A)	1098	1355	1 - 2.0
Cyclone	1.77 x 1.55 x 0.81	13 A (optional 20 A)	776	883	1 - 2.0
Whirlwind	1.98 x 1.98 x 0.86	13 A (optional 20 A)	1003	1166	1 - 2.0
Monsoon	2.06 x 1.60 x 0.84	13 A	890	1380	1 - 2.0
Hurricane	2.14 x 2.14 x 0.92	13 A	1136	1517	1 - 2.5
RZ420L	2.14 x 2.14 x 0.92	13 A	1300	1661	1-2.5
RZ340L	2.26 x 1.65 x 0.74	13 A	815	1240	1-2.5
Breeze	2.14 x 2.14 x 0.92	13 A	1136	1517	1 - 2.5
Tornado	2.14 x 2.14 x 0.92	32 A	1155	1563	1 - 2.5
Storm	2.26 x 2.26 x 0.92	32 A	1401	1873	1 - 2.5
Storm 96	2.26 x 2.26 x 0.92	32 A	1401	1873	1 - 2.5
RZ610L	2.26 x 2.26 x 0.92	32 A	1567	1972	2-2.5
RZ500L	2.14 x 2.14 x 0.92	32 A	1325	1691	2-2.5
RZ490NL	2.26 x 2.26 x 0.92	32 A	1365	1790	2-2.5
PLA-96L	2.26 x 2.26 x 0.92	20 A	1548	2448	2 - 2.5/2.5
PLA-80L	2.14 x 2.14 x 0.92	20 A	1250	2096	2 - 2.5/2.5
PLA-80NL	2.14 x 2.14 x 0.92	20 A	1250	2176	2 - 2.5/2.5
PLA-42L	2.14 x 2.14 x 0.92	20 A	1250	2137	1 - 2.5
PLA-42NL	2.14 x 2.14 x 0.92	20 A	1250	2217	1 - 2.5
PLA-34L	1.65 x 2.14 x 0.86	20 A	795	1334	1 - 2.5
PLA-40DL	2.14 x 2.14 x 0.92	20 A	1250	2100	1 - 2.5
PLA-42DL	2.14 x 2.14 x 0.92	20 A	1250	2100	1 - 2.5

CERTIFICATE

No. Z1A 015642 0162 Rev. 00

Model	Size L x W x H (m)	Input Current (A)	Water Capacity (L)	Mass Filled (kg)	No. of Pumps (Hp)
WLA-735L	2.13 x 2.13 x 0.91	16 A	1363	2103	2 – 2.0 / 2.0
WLA-735	2.13 x 2.13 x 0.91	16 A	1363	2103	2 – 2.0 / 2.0
WLA-845L	2.26 x 2.26 x 0.97	20 A	1514	2683	2 – 2.5 / 2.5
Vacationer Large L	2.13 x 2.13 x 0.89	20 A (optional 42 A)	250	2020	1 – 2.0
Vacationer Medium NL	2.00 x 1.85 x 0.89	20 A (optional 42 A)	1000	1675	1 – 2.0
Happy Lounge 25	2.08 x 1.96 x 0.84	13 A (optional 20 A)	961	1609	1 – 2.0
PLR-60S	2.21 x 1.96 x 0.86	13 A (optional 20 A)	882	1075	1 – 2.5
PLR-21S	1.98 x 1.98 x 0.86	13 A (optional 20 A)	1003	1148	1 – 2.0
PLR-13	1.78 x 1.55 x 0.81	13 A (optional 20 A)	776	900	1 – 2.0
PLR-64S	2.06 x 2.06 x 0.86	13 A	1098	1315	1 – 2.5
PLR-27S	2.06 x 1.83 x 0.86	13 A (optional 20 A)	1192	1383	1 – 2.0
PLR-24S	2.06 x 1.60 x 0.84	13 A (optional 20 A)	882	1043	1 – 2.0
PLR-10	1.83 x 1.19 x 0.71	13 A (optional 20 A)	450	565	1 – 2.0
PLR-44S	2.21 x 1.96 x 0.86	13 A	1098	1300	1 – 2.5
PLR-65S	2.06 x 2.06 x 0.86	13 A (optional 20 A)	1110	1315	1 – 2.5
PLR-65SL	2.21 x 1.96 x 0.86	13 A (optional 20 A)	1100	1300	1 – 2.5
C-32L	1.68 x 2.13 x 0.86	20 A	821	1332	1 – 2.0
S-32L	1.68 x 2.13 x 0.86	20 A	821	1332	1 – 2.0
C-40L	1.98 x 1.98 x 0.86	20 A	965	1682	1 – 2.0
S-40L	1.98 x 1.98 x 0.86	20 A	965	1682	1 – 2.0
C-40	1.98 x 1.98 x 0.86	20 A	1014	1889	1 – 2.0
S-40	1.98 x 1.98 x 0.86	20 A	1014	1889	1 – 2.0
C-72L	2.13 x 2.13 x 0.86	20 A (optional 32 A)	1219	2074	2 – 2.5
S-72L	2.13 x 2.13 x 0.86	20 A (optional 32 A)	1219	2074	2 – 2.5
C-72	2.13 x 2.13 x 0.86	20 A (optional 32 A)	1310	2244	2 – 2.5
S-72	2.13 x 2.13 x 0.86	20 A (optional 32 A)	1310	2244	2 – 2.5

Trademark: ISLANDER

- Model or Series name can be followed by suffix "E" or "EXP" to indicate exported models.

Model	Size L x W x H (m)	Input Current (A)	Water Capacity (L)	Mass Filled (kg)	No. of Pumps (Hp)
Kapiti	2.05 x 2.05 x 0.86	13 A (optional 20 A)	1003	1219	1 – 2.0
Matakana	2.21 x 1.96 x 0.86	13 A (optional 20 A)	1098	1292	1 – 2.0
Rangitoto	1.83 x 1.83 x 0.79	13 A (optional 20 A)	700	792	1 – 2.0
Tiritiri	1.78 x 1.55 x 0.81	13 A (optional 20 A)	776	898	1 – 2.0
Waiheke	2.13 x 2.31 x 0.91	32 A	1438	1833	2 – 2.5

Trademark: AQUATERRA

- Model or Series name can be followed by suffix "E" or "EXP" to indicate exported models.

Model	Size L x W x H (m)	Input Current (A)	Water Capacity (L)	Mass Filled (kg)	No. of Pumps (Hp)
Benicia	1.78 x 1.55 x 0.81	13 A (optional 20 A)	700	827	1 – 2.0
Transport II	1.90 x 1.90 x 0.86	13 A (optional 20 A)	927	1119	1 – 2.0
Verona	2.05 x 2.05 x 0.86	13 A (optional 20 A)	1192	1396	1 – 2.0
Montecito	2.05 x 2.05 x 0.86	13 A (optional 20 A)	1003	1219	1 – 2.0
Palisades	2.21 x 1.96 x 0.86	13 A (optional 20 A)	1098	1292	1 – 2.0
Aryana	2.21 x 1.96 x 0.86	13 A (optional 20 A)	1098	1309	1 – 2.0

CERTIFICATE

No. Z1A 015642 0162 Rev. 00

Newporter 3.0	1.98 x 1.98 x 0.86	13 A (optional 20 A)	1003	1166	1 – 2.0
Toscana II	1.83 x 1.83 x 0.79	13 A (optional 20 A)	700	792	1 – 2.0

Installation Requirements:

When installing the equipment, all requirements of the standard and manufacturer's specifications must be met. The equipment is for household use only & not for commercial application.

These models require:

1. The spa must be connected to a Ground Fault Circuit Interrupter (GFCI). The GFCI should be certified GFCI which complies with the particular national and local requirements. Always test the GFCI before use.
2. The Spas must be wired in accordance with applicable national and local electrical codes, all electrical work should be done by an experienced, licensed electrician.
3. The ground terminal should be bonded with a min 6 mm² (10 AWG) solid copper wire between this and unit and any metal ladders, metal water pipes etc within 1.5 m of the spa.
4. Prevent any electrical appliance within 1.5 m of the spa.

Manufacturer's Warning Statements / Missuse:

- Extreme caution must be exercised to prevent unauthorized access by children.
- Side effects of medication may increase by using the spa, consult a physician beforehand.
- Pregnant women or persons suffering from some kind of diseases should consult a physician before using spa.